


| 信号传输——M12, 带李兹线, 板前安装 | | 4芯 | | | |
|--|------------------------------------|---|---|---|---|
| 预装0.5 m长的李兹线  jh-com.com : #0207 | 防插错编码 | A | | D | |
| | 额定电压 标称电流 导线横截面 | 250 V 4 A 0.34 mm ² | | 250 V 4 A 0.34 mm ² | |
| | 针脚分配 |  |  |  |  |
| 带螺纹安装式铸铝外壳 | | | | | |
|  | Pg9 | 1693762 | 1693788 | - | - |
| | Pg9扁平螺母 | | | | |
|  | M16 x 1.5 | 1523450 | 1523434 | 1551558 | 1535202 |
| | M16 x 1.5扁平螺母 | | | | |
|  | M16 x 1.5, XL型, 扳手尺寸19 | 1411577 | 1411568 | 1411578 | 1411569 |
| | M16 x 1.5扁平螺母 | | | | |
|  | Pg9, 可定位 | 1693775 | 1693791 | - | - |
| | M16 x 1.5, 可定位 | 1523463 | 1523447 | 1552256 | 1535215 |
|  | 20 mm方方法兰, 安装孔 4 x Ø 3.2 mm | 1419784 | 1419797 | 1441626 | 1441639 |
| | 25 mm方方法兰, 安装孔 4 x Ø 2.7 mm | 1419991 | 1420003 | 1440957 | 1440960 |
| 带螺纹安装式塑料和黄铜（镀镍）外壳 | | | | | |
|  | 塑料 M16 x 1.5 | - | - | - | - |
| | 黄铜（镀镍） M20 x 1.5 | 1408451 | 1408436 | - | - |
| 带螺纹安装式不锈钢外壳（1.4404） | | | | | |
|  | Pg9 | 1554555 | 1554448 | - | - |
| | Pg9扁平螺母 | | | | |
|  | M16 x 1.5 | 1405233 | 1458855 | - | - |
| | M16 x 1.5扁平螺母 | | | | |
| | Pg9, 可定位 | 1554610 | 1554649 | - | - |
| | M20 x 1,5 | 1408415 | 1408416 | - | - |