



Electrical Character
 Rating voltage: 60V AC/DC
 Insulation resistance: >100MΩ
 Rating current: 4A
 Contact resistance: ≤5mΩ

General Information
 Standard: IEC 61076-2-101
 Connector Body: PA66+GF
 Contacts: Brass with gold plated
 Connector Locking System: Screw-locking
 Connector Screw: Brass with nickel plated
 Waterproof Ring: Fluorine rubber ring
 Waterproof Rating: IP67/IP68

UNDECLARED TOLERANCE		CUS P/N:	FLECONN PRECISION INDUSTRY (CHINA) CO., LIMITED			
X.±1.0	X.*±2.0°					
.X±0.5	.X*±1.0°	PART NO.:	TITLE:			
.XX±0.2	.XX*±0.5°	92032-01	M12 A Coding 5pin male connector front mount 90degree			
UNITS: MM		APPD.:	DWG NO.: D0043			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Fleconn AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF Fleconn.		CHKD.:		SCALE	SHEET	REV.
		DR.: HWJ_07/24/14'		1:1	1/1	A