





MOLD NO.	RFQ NO.: XXXXXX	REV.	DESCRIPTION	APPD.	DATE
		A	INITIAL RELEASED	WANG	11/09/19'

<http://connectors-cable.com>



- ③ 7/8 FEMALE TERMINAL GOLD PLATING OF COPPER ALLOY
- ② 7/8 5PIN MALE INSULATOR TPU(YELLOW)
- ① 7/8 FEMALE SHELL NICKEL PLATED BRASS

Detailed Product Description:

Waterproof connector rating is IP67

They can not be used permanently under water.

Connector Electrical character

Rating voltage: 300V ,

Insulation resistance: >100MΩ

Rating current : 9A

Contact resistance of connector ≤10mΩ

Mechanical characteristics: mating / cycle >100 cycle

Operating temperature: -25℃ ~ +85℃

*ALL MATERIALS ARE RoHS COMPLIANT.


<http://www.jh-com.com>

UNDECLARED TOLERANCE		CUS P/N:	骏慧兴业科技有限公司		
X. ±1.0	X. ° ±2.0°		Shenzhen JH-C Precision Technology CO		
.X ±0.5	.X ° ±1.0°	PART NO. :	TITLE:		
.XX ±0.2	.XX ° ±0.5°	92097-01	M12 D Coding		
UNITS: MM		APPD. :	DWG NO.: B00065		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JH-C AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF JH-C.		CHKD. :		SCALE	SHEET
		DR. : HWJ_09/11/19'		1:1	1/1
					REV.
					A

ITEM	PART NAME	DESCRIPTION	QTY
------	-----------	-------------	-----

F

F



- | | | | | | | | |
|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|---|---|---|---|---|---|---|---|

1		2		3		4		5		6		7		8		
MOLD NO.				RFQ NO. : XXXXXX						REV.	DESCRIPTION				APPD.	DATE
										A	INITIAL RELEASED				WANG	11/09/19'





1. 芯数/NO. of contacts

系列/Series	303	304	305
孔位排列/Pin Number			
适配线径/Conductor size	22AWG	22AWG	22AWG
导体直径/Pin size	1.0mm	1.0mm	1.0mm
额定电流/Rated current	4A	4A	4A
额定电压/Rated voltage	250V	250V	250V

3. 编码原则/Part Number

浮动式插头/Free Plug	M12A	I	305	A	F	L	B	G1
主型号/Type								
外观/Appearance: 1, 2, 3, 4								
针数/Pin Number								
绝缘体型号/Insulator coded: A, B, C								
绝缘体型号/Insulator type: P-Female								
针类型/Sold Type: L-Turning Y-Stamping								
针长度/Pin Length: B-Standard								
表面处理/Plating: Gold Flash								

<http://connectors-cable.com>



Electrical Character:
Rating voltage: 60V AC/DC
Insulation resistance: >100MΩ
Rating current: 4A
Contact resistance: ≤5mΩ

General Information:
Standard: IEC 61076-2-101
Connector Body: PA66
Contacts: Phosphorus copper with Gold plating
Connector Locking System:
Screw-locking (Brass)
Ambient Temperature: -25°C~+85°C
Waterproof Rating: IP67/IP68

<http://www.jh-com.com>

Connector Locking System: Screw-locking (Brass) Ambient Temperature: -25° C~+85° C Waterproof Rating: IP67/IP68				UNDECLARED TOLERANCE		CUS P/N:		骏慧兴业科技有限公司 Shenzhen JH-C Precision Technology CO					
				X. ±1.0	X. ° ±2.0°								
				.X±0.5	.X° ±1.0°	PART NO.:		TITLE:					
				.XX±0.2	.XX° ±0.5°	92083-01		M12 A Coding male solder connector					
						UNITS: MM		APPD.:		DWG NO.: B00065			
①		M12 A Coding 5pin male connector	1PCS	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JH-C AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF JH-C.		CHKD.:			SCALE	SHEET	REV.		
ITEM	PART NAME	DESCRIPTION	QTY			DR. : HWJ_09/11/19'			1:1	1/1	A		

1		2		3		4		5		6		7		8		
MOLD NO.				RFQ NO. : XXXXXX						REV.	DESCRIPTION				APPD.	DATE
										A	INITIAL RELEASED				WANG	11/09/19'





1. 芯数/NO. of contacts

系列/Series	303	304	305
孔位排列/Pin Number			
导体规格/Conductor size	22AWG	22AWG	22AWG
导体直径/Pin size	1.0mm	1.0mm	1.0mm
额定电流/Rated current	4A	4A	4A
额定电压/Rated voltage	250V	250V	300V

<http://connectors-cable.com>

3. 编码原则/Part Number

浮动式插头/Free Plug	M12A I 305 A F L B G1
主型号/Type	
外观/Appearance: 1, 2, 3, 4	
针数/Pin Number	
绝缘体型号/Insulator coded: A, B, D	
绝缘体型号/Insulator type: P-Pomile	
针类型/Sold Type: L-Turning Y-Stamping	
针长度/Pin Length: B-Standard	
表面处理/Plating: Gold Flash	



Electrical Character:

Rating voltage: 60V AC/DC

Insulation resistance: >100M Ω

Rating current: 4A

Contact resistance: $\leq 5m\Omega$

General Information:

Standard: IEC 61076-2-101

Connector Body: PA66+GF

Contacts: Phosphorus copper with Gold plating

Connector Locking System: Screw-locking

(Brass)


(Brass plating salt spray pass for 48 hours)

Ambient Temperature: -25 $^{\circ}$ C~+85 $^{\circ}$ C

Waterproof Rating: IP67/IP68

<http://www.jh-com.com>

(Brass) (Brass plating salt spray pass for 48 hours) Ambient Temperature: -25° C~+85° C Waterproof Rating: IP67/IP68				UNDECLARED TOLERANCE		CUS P/N:		骏慧兴业科技有限公司			
				X. ±1.0		X. ° ±2.0°		Shenzhen JH-C Precision Technology CO			
				.X±0.5		.X° ±1.0°		PART NO.: 92082-01		TITLE: M12 A Coding 5Pin female solder connector	
				.XX±0.2		.XX° ±0.5°					
③		Nut 14.5*10.7mm Brass with nickel plated	1PCS	UNITS: MM		APPD.:		DWG NO. B00066:			
②		Green Fluorine rubber ring Ø7*1.0mm	1PCS	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JH-C AND SHALL NOT BE REPRODUCED,COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF JH-C.		CHKD.:			SCALE	SHEET	REV.
①		M12 A Coding 5pin female connector	1PCS			DR. : HWJ_09/11/19'			1:1	1/1	A
ITEM	PART NAME	DESCRIPTION	QTY								





RJ45工业以太网连接器

<http://connectors-cable.com>

- 全屏蔽高性能工业以太网连接器适用于CAT5E、CAT6、CAT7各类网线
- 支持工业以太网 (1000Base-T)高速传输
- 符合EtherCAT、EtherNET、PROFINET、CC-LINK IE Field标准
- 加工方式: 压接刺破式


EtherCAT



- 额定电流 1A max
- 额定电压 30V DC
- 绝缘阻抗 500M Ohm
- 工作温度 -40°C~+70°C
- 胶芯材质 PBT UL94V-0 黑
- 外壳材质 铜合金
- 接触材质 铜合金/镀金
- 适用线规 最大外径7.0mm


- Rated current 1A max
- Rated voltage 30V DV
- Insulation impedance 500M Ohm
- working temperature -40°C~70°C
- HSG material PBT UL94-0
- Shielding material Copper alloy
- Contact pin Gold plating on brass
- Suitable CABLE diameter 7.0 Max

<http://connectors-cable.com>




8P4C

8POS, Active 6,3,2,1



8P8C



<http://connectors-cable.com>

产品型号	芯数	适用线规	适用线径	芯线直径	备注
RJ45-8P8C-IDC	8	24AWG-26AWG	7mm	1.2以下	刺破加工
RJ45-8P4C-IDC	4	24AWG-26AWG	7mm	1.2以下	刺破加工

<http://www.jh-com.com>